

Wire feeders

Model number	YW-20DGD1*1	YW-35DG1	YW-35DG1TAK	YW-40DG1	YW-40DG1TAK (Air-cooled)	YW-40DGW1TAK (Water-cooled)
Torch connection	CC fitting connection type					
Rated current	200 A	350 A	350 A	400 A	400 A	400 A
Applicable wire type	Mild steel / Flux cored mild steel / Stainless / Flux cored stainless steel / MIG blaze		Aluminum	Mild steel / Stainless	Aluminum	
Applicable wire diameter	0.8 / 0.9 / (1.0) / (1.2) mm*2	(0.8) / (0.9) / 1.0 / 1.2 mm*2	1.2 mm	0.9 / (1.0) / 1.2 / (1.4) mm*2	1.2 / 1.6 mm	1.2 / 1.6 mm
Drive system	1 driven roll and 1 idler roll	2 driven rolls and 2 idler rolls	4 driven rolls	2 driven rolls and 2 idler rolls	4 driven rolls	
Spool shaft	Fixed type		Equipped with brake			
Cable and hose length	Control cable / Power cable: 6 m, Gas hose: 9.2 m	Control cable / Power cable: 1.8 m, Gas hose: 4.8 m				
Mass	17 kg	12 kg	14 kg	12.5 kg	15 kg	18 kg

*1 : Applicable wire diameter for YW-20DGD1TAM: ϕ 0.6 / 0.8 / (1.0) / (1.2) mm

*2: Diameters in () can be used with optional parts.