

Welding torches (CC fitting connection)

Model number	Rated current (A)	Cooling type	Rated duty cycle (%)	Applicable wire diameter (mm)	Cable length (m)	Remarks
YT-20CS4TAB	200	Air-cooled	50 (CO ₂) / 25 (MAG)	(0.8) / 0.9 / (1.0) / (1.2)	3	
YT-35CE4TAB	350	Air-cooled	20 (CO ₂) / 20 (MAG)	(0.9) / (1.0) / 1.2	3	Lightweight type
YT-35CS4TAB	350	Air-cooled	45 (CO ₂) / 35 (MAG)	(0.9) / (1.0) / 1.2 / (1.4)	3	
YT-50CS4TAB	500	Air-cooled	40 (CO ₂) / 35 (MAG)	(1.2) / 1.4 / (1.6)	3	
YT-50CSG4TAB	500	Air-cooled	20 (Pulsed MAG: 350A)	(1.2) / 1.4 / (1.6)	3	For Pulsed MAG
YT-20MD2	200	Air-cooled	30 (Pulsed MIG) / 60 (MIG)	(1.0) / 1.2	3	For Aluminum
YT-30MD2	300	Air-cooled	30 (Pulsed MIG) / 50 (MIG)	(1.0) / 1.2 / (1.6)	3	For Aluminum
YT-40MDW2	400	Water-cooled	60 (Pulsed MIG) / 100 (MIG)	1.2 / (1.6)	3	For Aluminum
YT-50MDW2	500	Water-cooled	60 (Pulsed MIG) / 80 (MIG)	(1.2) / 1.6	3	For Aluminum

*Optional parts are required to use the wire sizes in ().

*Rated duty cycle is based on JIS standard